

T8 8FT LED Tube Light Type B

Approvals

Certification



UL

Universal Compatibility

High efficiency, energy saving, mercury free.
Also work directly from 100-277VAC.

Good Retrofit Choice

 120° wide beam angle and 110lm/w high efficacy make it an ideal retrofit option for users.

Design

 Made by half aluminum and half plastic, good heat dissipation.

Warranty: 5 years

Life Span: 50,000Hrs

Applications







Hospital



School

Office



3

Supermarket

Retail

Factory



FA8

end

1. Product Dimension



| Product Length | Total Length(mm) | Cap-Base |
|----------------|------------------|----------|
| 8FT | 2368+/-1 | FA8 |

2. Environment & Electrical characteristics

Humidity

Temperature

Input voltage: AC100-277V, 50Hz/60Hz

Operating10%-80% Storage 10%-80% Operating -20~+40 $^{\circ}$ C Storage -40~+60 $^{\circ}$ C


PF :> 0.9, THD<20% (With EB)

Power efficiency: 90%

T8 LED Tube - Normal efficiency

| Item | Wattage | LED Q'TY | ССТ | Luminous Flux | Beam Angle | Cover | Length (mm) | Certificate |
|-----------------------|---------|-------------|-------|------------------|---------------|---------|----------------|-------------|
| DJ-T88F40W- 4000KF | 40W | 220pcs | 4000K | 4400LM±10% | 120° | Frosted | 2368+/-1 | UL |
| DJ-T88F40W- 5000KF | | 2835LEDs | 5000K | 4400LM±10% | 120° | Frosted | | |

3. Installation Guide



More information about installation & specification, please contact our services.